



Technical drawing of a mechanical assembly, showing two views: a top view (left) and a side view (right).

Top View Dimensions:

- Overall length: 282.7
- Distance from left end to center of circular feature: 252.5
- Distance from left end to center of shaft: 220
- Radius of circular feature: 65

Side View Dimensions:

- Overall length: 282.7
- Distance from left end to center of shaft: 82.5
- Distance from center of shaft to center of circular feature: 102
- Distance from center of shaft to right end: 98.2
- Radius of circular feature: 72.5
- Distance from left end to center of shaft: 98
- Distance from center of shaft to right end: 98
- Distance from left end to center of circular feature: 130
- Distance from center of shaft to right end: 182

Callouts:

- 1: Circular feature (top view)
- 2: Circular feature (side view)
- 3: Circular feature (top view)
- 4: Circular feature (side view)
- 5: Circular feature (top view)
- 6: Circular feature (side view)
- 7: Circular feature (top view)
- 8: Circular feature (side view)
- 9: Circular feature (top view)
- 10: Circular feature (side view)
- 11: Circular feature (top view)
- 12: Circular feature (side view)
- 13: Circular feature (top view)
- 14: Circular feature (side view)
- 15: Circular feature (top view)

15	注意喚起シール	1				
14	波型スプリングピン一般用	2	ステンレス	生地脱脂	呼び4×50	
13	ジョイント固定ナット	2	ステンレス	生地脱脂	六角ナットM6 ナイロン緩み止め	
12	平座金	2	ステンレス	生地脱脂	呼び6	
品番	名 称	数量	材 質	表 面 処 理	備 考	
記 事				名 称	たよレールアップU 組図	製 図 月 日
				図 番		尺 度

承 認	☐	検 図	☐	設 計	☐	製 図	☐
1/2		マツロク株式会社 MAZROC CO., LTD.					